

Tejas
Margapuram

Observatory Automation & Remote Control

✦ Supervisor:
Dr Yang Yang



THERE'S NOT ↗
MUCH SPACE
***IN SPACE.* ★**



- Over 11,000 active satellites
- Over 40,000 tracked objects
- Over 130 million pieces of junk in orbit < 1mm

~ 7.8km/s orbital speed

**NEED eyes on the ground
to track debris**



The observatories need brains




- Space Situational Awareness (SSA) requires automation
 - Point and track objects automatically

The HQ: K17 Rooftop

Sitting atop the Computer Science and Engineering (CSE) Building, sits the UNSW observatory.

Ideally, this observatory joins the global SSA effort.



So, what's in there?





The Eye

Schmidt-Cassegrain Optical Telescope




Aperture
35cm



Focal Length
391mm



Focal Ratio
f/11



Field of View (FoV)
 $0.17^{\circ} \times 0.17^{\circ}$

The Muscle

10Micron GM2000 HPS II

A German-Equatorial mount built like a tank




Absolute Encoders	Satellite Tracking Capability	50kg Payload Capacity
TCP/IP with Ethernet OR WiFi	Serial Connection with ASCOM	Sub Arcsecond Precision

Image links: <https://thefrisky.com/wp-content/uploads/2019/01/musculacion.jpg>
<https://www.10micron.com/wp-content/uploads/2016/03/GM1000HPS-05-1.jpg>

The Retina

ZWO ASI 533MM



➤ Monochromatic, high-speed CMOS sensor for orbital capture





**Okay,
How do we use it?**



★It needs some babysitting



**The telescope system is great.
The infrastructure was... vintage.**

- Manual dome
- Manual shutter
- No sensors
- No control software
- No central computer

Reality check


Most educational observatories are like this

- Built for a different era
- Dormant, but powerful equipment just asking to enter the modern world
 - SSA
 - Better Educational Tooling



Project Goal

Build a fully remotely usable, automatable system for:



↗ Telescope Control _____

↗ Dome + Shutter Control _____

↗ Live Feedback _____

How did I even start?

**A systems engineering
approach**



Requirements



Install Hardware




Write Software



Hardware + Software Integration





Testing, Verification & Validation



System Architecture

Hardware Installs



Replacement of the 240V AC motor assembly with a DC motor



Control computer installation (temporarily just my laptop)

Telescope Mount Driver

Talking to the mount without Google Translate



Handles communication and translation

I wrote a 1400 line Python package to cover all important mount functionality

Communicates over TCP/IP Sockets via Ethernet

Taming the Dome

The dome firmware is like a forgetful, hearing-impaired person



Runs over UDP and IR

Drops frames frequently

Custom low-level protocol

Under active development (changing)

The Brain

The glue holding it all together and doing the thinking




Python + FastAPI powered backend

Websockets & REST API



Non-blocking calls with AsyncIO

Integrated documentation




Pydantic data validation for safety

Runs integration logic such as...



The math of seeing

Dome Synchronisation



➤ Off-Centre

The telescope mount isn't in the centre of the dome

➤ Changing Pivot

German-Equatorial Mounts have 2 independent axes other than the telescope optical axis

➤ Meridian Flips

German-Equatorial mounts can flip pier side but point to the same location

Dashboard

**Where everything is
controlled from**



Control Point



React and Typescript



View stats and show live
telemetry



Show camera view of
observatory

08

Kerbal Space Program 3D Visualiser




Shows mount and telescope orientation

Shows dome slit orientation

Shutter status

Yeah, but does it actually work?



Unit Tests	Software Integration Tests	Hardware-In-Loop Tests
Frontend Usability Tests	End-to-end Operation Tests	But not just that...

Live Demo!




Here we go...

Yeah, pretty much!



- Stable mount control achieved
- Dome synchronisation worked for the two quadrants tested
 - Dome firmware functionality limited
 - The firmware was only completed by a collaborator a few weeks ago
- <300ms local latency
 - Remote latency is variable
- Complete remote control works too!





09



Educational Benefit

- Remote Learning
- Safe student access
- Real-time interaction
- Visual engagement


SSA & Research Impact



- LEO tracking potential
- TLE-based satellite mode
- Automated observation workflows



So what next?



➤ **Hardware Integration**

Shutter control
Weather station
Telescope sensor

➤ **Computer Installation**

Install a central computer
Install data processing node

➤ **Make a robot(ic observatory)**

Ai assisted task scheduling
Closed-loop image analysis
Automatic SSA node

Thank You

